

NPC-Series - Valve Regulated Lead Acid Battery NPC38-12I

| SPECIFICATIONS | | |
|---|---|--------------|
| Nominal voltage | 12 | V |
| 20-hr rate Capacity to 10.5V at 20°C | 38 | Ah |
| 10-hr rate Capacity to 10.8V at 20°C | 33.44 | Ah |
| DIMENSIONS | | |
| Length | 197 (±0.5) | mm |
| Width | 165 (±0.5) | mm |
| Height | 170 (±0.5) | mm |
| (height over terminals) | N/A | mm |
| Mass (typical) | 14.0 | kg |
| TERMINAL TYPE | | |
| Female threaded terminal | M5 | mm |
| Torque | 2.5 | Nm |
| OPERATING TEMPERATURE RANGE | | |
| Storage | -20°C to +60°C | |
| Charge | -15°C to +50°C | |
| Discharge | -20°C to +60°C | |
| STORAGE | | |
| Capacity loss per month at 20°C (approx) | 3 | % |
| CASE MATERIAL | | |
| Standard Option | ABS (UL.94:HB) | |
| Flame retardant option (FR) | N/A | |
| CHARGE VOLTAGE | | |
| Float charge voltage at 20°C | 13.65 (±1%) | V |
| | 2.275 (±1%) | V/cell |
| Float Charge voltage temperature correction factor (for variations from the standard 20°C) | -3 | mV/cell/°C |
| Cyclic (or Boost) charge at 20°C | 14.5 (±3%) | V |
| | 2.42 (±3%) | V/cell |
| Cyclic Charge voltage temperature correction factor (for variations from the standard 20°C) | -4 | mV/cell/°C |
| CHARGE CURRENT | | |
| Float charge current limit | No limit | A |
| Cyclic (or Boost) charge current limit | 9.50 | A |
| MAXIMUM DISCHARGE CURRENT | | |
| 1 second | 500 | A |
| 1 minute | 380 | A |
| SHORT-CIRCUIT CURRENT & INTERNAL RESISTANCE (according to EN IEC 60896-21) | | |
| Internal resistance | N/A | mΩ |
| Short-Circuit current | N/A | A |
| CYCLIC LIFE DATA | | |
| 100% DOD down to 80% capacity | 300 | cycles |
| 75% DOD down to 80% capacity | 500 | cycles |
| 50% DOD down to 80% capacity | 600 | cycles |
| 25% DOD down to 80% capacity | 1400 | cycles |
| IMPEDANCE | | |
| Measured at 1 kHz | 7.3 | mΩ |
| PERFORMANCE & CHARACTERISTICS | | |
| Refer to the technical manual | NPC | |
| DESIGN LIFE | | |
| EUROBAT Classification: Standard Commercial Life data: e.g. 600 cycles at 50% DOD | Cycle | 3 to 5 years |
| SAFETY | | |
| Installation | Can be installed and operated in any orientation except permanently inverted | |
| Handles | Batteries must not be suspended by their handles (where fitted) | |
| Vent valves | Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal. | |
| Gas Release | VRLA Batteries release hydrogen gas which can form explosive mixtures in air. Do not place inside a sealed container | |
| Recycling | YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations | |



LAYOUT



3RD PARTY CERTIFICATIONS

ISO 9001 - Quality Management Systems
 ISO 14001 - Environmental Management Systems
 EN 18001 - OHSAS Management Systems
 ISO 9001 - Quality Management Systems



UNDERWRITERS LABORATORIES Inc.

STANDARDS

IEC61056



ALL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE
 Issue No.: V.1 / Issue Date: July 2010



YUASA BATTERY SALES UK LTD.
 Unit 22
 Rassau Industrial Estate
 Ebbw Vale, Gwent
 NP23 5SD
 UK